

Automotive Sensor Products

Seat Occupancy Sensor – Reed



General Description

The Seat Occupancy sensor is a magnetically operated push button sensor with a simple push-fit clip mounting configuration, allowing the passenger safety system to determine the presence of an object or person in a seat.

Operation

Basic Principle

The sensor is in a normally open position. When the plunger is depressed the magnetic circuit will be complete, activating the Reed Switch to close its contacts sending a voltage output to the customer electrical interface.

Packaging Options

Custom packaging can be provided to meet any need, please contact Littelfuse Engineering for details.

Features

- ♦ Magnetically operated position sensor
- ♦ Simple flush and recessed mounting options available
- ♦ Normally open contact
- ♦ Operates when plunger is depressed
- ♦ Choice of cable length and clips
- ♦ Choice of connector and terminals
- ♦ Choice of circuitry for output voltages

Benefits

- ♦ Robust construction makes this sensor well suited to harsh environments
- ♦ No standby power required
- ♦ Integral neoprene boot provides protection from severe environments
- ♦ Hermetically sealed, magnetically operated contacts give excellent life and reliability
- ♦ Can be connected directly to sounder or LED indicator

Applications

- ♦ Seat occupancy
- ♦ Position and limit sensing

Automotive Sensor Products

Functional Characteristics

Parameter			
Type			
Reed Switch Sensor			
Contact			Normally Open
Electrical			
Voltage	Switching	Max.	200V _{dc} / 140V _{ac} RMS 250 V _{dc}
	Breakdown	Min.	
Current	Switching	Max.	0.5A _{dc} / 0.35A _{ac} RMS
	Carry	Max.	0.5A _{dc} / 0.35A _{ac} RMS
Rating	Power	Max.	10W
Resistance	Contact, Initial	Max.	0.12 Ω
	Insulation	Max.	10 ¹² Ω
Capacitance	Contact	Typ.	0.2pF
Environmental/Mechanical			
Temperature	Operating	Celsius	-40° to +105°
	Storage	Celsius	-65° to 105°
Shock	11ms ½ Sine	Max.	100g

Littelfuse

Website: www.littelfuse.com
 Sales Support: ALL_Autosensors_Sales@littelfuse.com
 Technical Support: ALL_Autosensors_Tech@littelfuse.com

Information provided by Littelfuse is believed to be accurate and reliable.
 All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
 Littelfuse products are designed for specific applications and should not be used for any purpose (including, without limitation, automotive applications) not expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse product documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse product documentation.