

1	COMPONENT NO		550	CDIDTION	OTV/M	11/84
NO	COMPONENT NO		DESCRIPTION		QTY/M	U/M
BILL OF MATERIAL						
<s></s>		CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE				
•		DENOTES CRITICAL CHARACTERISTICS.				
СРК		DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE				
<u>(ST)</u>		DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.				
СР		DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.				
MATL :	SPEC			FINISH		
DRW myork		DATE	SCALE NTS	FINISH GOOD WT		
		1/11/2023		GRAMS/PIECE		
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994						
	O ANGLE DJECTION					

Littelfuse® CHICAGO, ILLINOIS 60631

REVISION DRWG NO. A OL-LDSCE11

DOUBLE KEY LOCK DEVICE 100-200A OUTLINE