


# 382 Series

## TR5® Fuse, Time-Lag



### Additional Information



Resources



Accessories



Samples

### Description

The 382 Series are TE5 Time-Lag type Fuses, 250V rated, with enhanced breaking capacity and designed in accordance to IEC 60127-3.

### Features & Benefits

- Halogen free, Lead-free and RoHS compliant
- Reduced PCB space requirements
- Direct solderable or plug-in versions
- 100A breaking capacity
- Internationally approved
- Low internal resistance
- Shock safe casing
- Vibration resistant
- Available from 1A to 10A
- UL Recognized to UL/CSA/NMX 248-1 and UL/CSA/NMX 248-14
- Conforms to EN/IEC 60127-1 and EN/IEC 60127-3
- Conforms to J60127-1 and J60127-3
- Conforms to K60127-1 and K60127-3
- Conforms to GB/T9364.1 and GB/T9364.3

### Applications

- Battery Chargers
- Consumer Electronics
- Power supplies
- Industrial Controllers

### Agency Approvals

| Agency | Agency File Number | Ampere Range |
|--------|--------------------|--------------|
|        | 40018249           | 1A - 4A      |
|        | 40018250           | 5A - 6.3A    |
|        | E67006             | 1A - 10A     |
|        | NBK040322-JP1021   | 1 - 5A       |
|        | NBK200122-JP1021   | 6.3 - 10A    |
|        | 2020970207000057   | 1A - 6.3A    |
|        | SU05024-7003       | 1-2.5A       |
|        | SU05024-7002       | 3.15A        |
|        | SU05024-7001       | 4A           |
|        | SU05024-7004       | 5A           |
|        | SU05024-7005       | 6.3A         |
|        | NA                 | 1A - 6.3A    |
|        | NA                 | 1A - 6.3A    |
|        | NA                 | 1A - 6.3A    |

### Electrical Characteristics

| % of Ampere Rating | Opening Time                    |                                |
|--------------------|---------------------------------|--------------------------------|
|                    | 1A - 6.3A                       | 8A - 10A                       |
| 150%               | 1 Hour, Min.                    | 1 Hour, Min.                   |
| 210%               | 2 Minutes, Max.                 | 300 s, Max.                    |
| 275%               | 400 ms, Min. ;<br>10 Sec., Max. | 1 s, Min. ; 20 s, Max.         |
| 400%               | 150 ms, Min. ;<br>3 Sec., Max.  | 150 ms, Min. ;<br>3 Sec., Max. |
| 1000%              | 20 ms, Min. ; 150 ms, Max.      | 20 ms, Min. ; 150 ms, Max.     |

# 382 Series

## TR5® Fuse, Time-Lag


### Electrical Characteristics

| Amp Code | Rated Current | Voltage Rating | Breaking Capacity <sup>3</sup> | Nominal Cold Resistance (Ohms) <sup>2</sup> | Voltage Drop 1.0xI <sub>N</sub> max. (mV) | Power Dissipation 1.5xI <sub>N</sub> max. (mW) | Melting Integral 10xI <sub>N</sub> min. (A <sup>2</sup> s) | Agency Approvals |       |    |   |    |    |     |
|----------|---------------|----------------|--------------------------------|---------------------------------------------|-------------------------------------------|------------------------------------------------|------------------------------------------------------------|------------------|-------|----|---|----|----|-----|
|          |               |                |                                |                                             |                                           |                                                |                                                            | CE               | UK CA | DV | c | UL | PS | CCC |
| 1100     | 1.00 A        | 250 V          | 100A @250VAC                   | 0.0625                                      | 100                                       | 400                                            | 4.85                                                       | X                | X     | X  | X | X  | X  | X   |
| 1125     | 1.25 A        | 250 V          |                                | 0.0500                                      | 95                                        | 465                                            | 6.88                                                       | X                | X     | X  | X | X  | X  | X   |
| 1160     | 1.60 A        | 250 V          |                                | 0.0377                                      | 90                                        | 490                                            | 12.67                                                      | X                | X     | X  | X | X  | X  | X   |
| 1200     | 2.00 A        | 250 V          |                                | 0.0280                                      | 85                                        | 670                                            | 17.80                                                      | X                | X     | X  | X | X  | X  | X   |
| 1250     | 2.50 A        | 250 V          |                                | 0.0215                                      | 80                                        | 750                                            | 29.69                                                      | X                | X     | X  | X | X  | X  | X   |
| 1315     | 3.15 A        | 250 V          |                                | 0.0176                                      | 75                                        | 900                                            | 45.35                                                      | X                | X     | X  | X | X  | X  | X   |
| 1400     | 4.00 A        | 250 V          |                                | 0.0138                                      | 70                                        | 1200                                           | 72.00                                                      | X                | X     | X  | X | X  | X  | X   |
| 1500     | 5.00 A        | 250 V          |                                | 0.0108                                      | 65                                        | 1250                                           | 121.25                                                     | X                | X     | X  | X | X  | X  | X   |
| 1630     | 6.30 A        | 250 V          |                                | 0.0076                                      | 65                                        | 1400                                           | 148.84                                                     | X                | X     | X  | X | X  | X  | X   |
| 1800     | 8.00 A        | 250 V          |                                | 0.0059                                      | 63                                        | 1600                                           | 233.60                                                     | -                | -     | -  | X | X  | -  | -   |
| 2100     | 10.00 A       | 250 V          |                                | 0.0042                                      | 57                                        | 1600                                           | 365.00                                                     | -                | -     | -  | X | X  | -  | -   |

#### Notes:

1. 1.00 means the number one with two decimal places. 1,000 means the number one thousand.
2. Resistance is measured at 10% of rated current, 25°C.
3. Breaking Capacity may differ based on Agency Approval. See Agency Approval certificate for more details.


### Temperature Derating Curve



#### Note:

1. Derating depicted in this curve is in addition to the standard derating of 25% for continuous operation.


### Average Time Current Curves



# 382 Series

## TR5® Fuse, Time-Lag

### Soldering Parameters - Wave Soldering



### Recommended Process Parameters:

| Wave Parameter                                       | Lead-Free Recommendation          |
|------------------------------------------------------|-----------------------------------|
| Preheat:<br>(Depends on Flux Activation Temperature) | (Typical Industry Recommendation) |
| Temperature Minimum:                                 | 100°C                             |
| Temperature Maximum:                                 | 150°C                             |
| Preheat Time:                                        | 60-180 seconds                    |
| Solder Pot Temperature:                              | 260°C Maximum                     |
| Solder Dwell Time:                                   | 2-5 seconds                       |

### Recommended Hand-Solder Parameters:

Solder Iron Temperature: 350°C +/- 5°C  
Heating Time: 5 seconds max.


**Note:** These devices are not recommended for IR or Convection Reflow process.

### Product Characteristics

|                                  |                                                                                                |
|----------------------------------|------------------------------------------------------------------------------------------------|
| <b>Materials</b>                 | Base/Cap: Brown Thermoplastic<br>Polyamide PA 6.6, UL 94 V-0<br>Round Pins: Copper, Tin-plated |
| <b>Lead Pull Strength</b>        | 10 N (IEC 60068-2-21)                                                                          |
| <b>Solderability</b>             | 260°C, ≤ 3s. (Wave)<br>350°C, ≤ 1s. (Soldering Iron)                                           |
| <b>Soldering Heat Resistance</b> | 260°C, 10s. (IEC 60068-2-20)<br>350°C, 3s. (Soldering Iron)                                    |

|                              |                                                                                                                      |
|------------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>Operating Temperature</b> | -40°C to +85°C (consider re-rating)                                                                                  |
| <b>Climatic Category</b>     | -40°C to +85°C /21 days<br>(IEC 60068-1,-2-1,-2-2,-2-78)                                                             |
| <b>Stock Conditions</b>      | +10°C to +60°C<br>RH ≤ 75% yearly average, without dew, maximum value for 30 days-95%                                |
| <b>Vibration Resistance</b>  | 24 cycles at 15 min. each<br>(IEC 60068-2-6)<br>10 - 60 Hz at 0.75 mm amplitude<br>60 - 2000 Hz at 10 g acceleration |

### Dimensions (mm)



Long Leads (L=18.8mm ±0.3)  
Short Leads (L=4.3mm ±0.3)

Holes in PCB

### Part Numbering System

**382    xxxx    0000**

**Series**

**Amp Code**

Refer to Amp Code column of  
Electrical Characteristics Table

**Packaging Code**

0000 Tape/Ammopack (1,000 pcs.)  
0410 Short Leads - Bulk (1,000 pcs.)  
0430 Short Leads - Bulk (200 pcs.)

### Packaging

| Packaging Option  | Packaging Specification | Quantity | Quantity & Packaging Code | Taping Width |
|-------------------|-------------------------|----------|---------------------------|--------------|
| <b>382 Series</b> |                         |          |                           |              |
| Tape & Ammopack   | N/A                     | 1,000    | 0000                      | N/A          |
| Short Leads       | N/A                     | 1,000    | 0410                      | N/A          |
| Short Leads       | N/A                     | 200      | 0430                      | N/A          |

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).