LSIC2SD120C08A
1200 V, 8 A SiC Schottky Barrier Diode



Agency Approvals and Environmental

Environmental Approvals
RoHS Pb HF

Pinout Diagram



Product Summary

Characteristic	Value	Unit
V_{RRM}	1200	V
I_F ($T_C \leq 135$ °C)	12.5	A
Q_C (V_R: 0-800 V)	47	nC

Features

- AEC-Q101 Qualified
- MSL 1 Rated
- Positive temperature coefficient for safe operation and ease of paralleling
- 175 °C maximum operating junction temperature
- Excellent surge capability
- Extremely fast, temperature-independent switching behavior
- Dramatically reduced switching losses compared to Si bipolar diodes
- RoHS compliant, lead-free, and halogen-free

Applications

- Boost diodes in PFC or DC/DC stages
- Switch-mode power supplies
- Solar inverters
- Uninterruptable power supplies
- Industrial motor drives
- Battery Chargers
- High speed rectifier

Specifications are subject to change without notice.
Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics
© 2021 Littelfuse, Inc.
Revised: 3/1/2021

1. Maximum Ratings....3
2. Thermal Characteristics....3
3. Electrical Characteristics....3
4. Performance Curves....4
5. V_F Model for Simulation....5
6. Package Dimensions....6
7. Part Numbering and Marking....6
8. Packing Options....6
9. Packing Specifications....7

Specifications are subject to change without notice.
Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics
© 2021 Littelfuse, Inc.
Revised: 3/1/2021

1. Maximum Ratings

Characteristic	Symbol	Conditions	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	-	1200	V
DC Blocking Voltage	V_R	-	1200	V
Continuous Forward Current	I_F	T_C = 25 °C	24.0	A
		T_C = 135 °C	12.5	
		T_C = 154 °C	8	
Non-repetitive Forward Surge Current	I_{FSM}	T_C = 25 °C, t_p = 10 ms, Half sine pulse	65	A
I^2t	$\int I^2dt$	T_C = 25 °C, t_p = 10 ms, Half sine pulse	21	A^2s
Power Dissipation	P_{Tot}	T_C = 25 °C	125	W
		T_C = 110 °C	54	
Operating Junction Temperature	T_J	-	-55 to 175	°C
Storage Temperature	T_{STG}	-	-55 to 150	°C
Lead Temperature for Soldering (MSL 1 Rated)	T_{SOLD}	-	260	°C

2. Thermal Characteristics

Characteristic	Symbol	Value	Unit
Maximum Thermal Resistance, junction-to-case	$R_{th,JC,MAX}$	1.2	°C/W

3. Electrical Characteristics

Characteristic	Symbol	Conditions	Value			Unit
			Min	Typ	Max	
Forward Voltage	V_F	I_F = 8 A, T_J = 25 °C	-	1.5	1.8	V
		I_F = 8 A, T_J = 175 °C	-	2.1	-	
Reverse Current	I_R	V_R = 1200 V, T_J = 25 °C	-	<1	100	µA
		V_R = 1200 V, T_J = 175 °C	-	3	-	
Total Capacitance	C	V_R = 1 V, f = 1 MHz	-	455	-	pF
		V_R = 400 V, f = 1 MHz	-	45	-	
		V_R = 800 V, f = 1 MHz	-	33	-	
Total Capacitive Charge	Q_C	V_R = 800 V, $Q_C = \int C(V)\,dV$	-	47	-	nC
Capacitance Stored Energy	E_C	V_R = 800 V	-	10.6	-	µJ

Littelfuse Expertise Applied | Answers Delivered
IXYS A Littelfuse Technology
Specifications are subject to change without notice.
Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics
© 2021 Littelfuse, Inc.
Revised: 3/1/2021

4. Performance Curves

Figure 1. Typical Forward Characteristics



Figure 2. Typical Reverse Characteristics



Figure 3. Power Derating



Figure 4. Current Derating



Figure 5. Capacitance vs. Reverse Voltage



Figure 6. Capacitive Charge vs. Reverse Voltage



Littelfuse Expertise Applied | Answers Delivered
IXYS A Littelfuse Technology
Specifications are subject to change without notice.
Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics
© 2021 Littelfuse, Inc.
Revised: 3/1/2021

Figure 7. Stored Energy vs. Reverse Voltage



Figure 8. Transient Thermal Impedance



5. V_F Model for Simulation



$$V_F(T_J) = V_0 + IR_0$$
$$V_0 = -1.20 \times 10^{-3} \cdot T_J + 9.88 \times 10^{-1}$$
$$R_0 = 2.05 \times 10^{-6} \cdot T_J^2 + 3.38 \times 10^{-4} \cdot T_J + 5.61 \times 10^{-2}$$

Notes:

- T_J is junction temperature in °C
- Range valid from 25 °C to 175 °C
- Model represents performance of a typical part

Littelfuse Expertise Applied | Answers Delivered
IXYS A Littelfuse Technology
Specifications are subject to change without notice.
Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics
© 2021 Littelfuse, Inc.
Revised: 3/1/2021

6. Package Dimensions



NOTE:
1. L4 – MAXIMUM PLASTIC PROTRUSION.
2. L2 – REFERENCE FOR FOOT LENGTH MEASUREMENT.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS B3, L3, D1, AND E1
4. PACKAGE OUTLINE D AND E EXCLUSIVE OF ANY MOLD FLASHES DIMENSIONS.
5. PACKAGE OUTLINE D AND E EXCLUSIVE OF ANY BURR DIMENSIONS.
6. FOR SINGLE-GAUGE LEADFRAME.

Symbol	Millimeters	
	Min	Max
A	2.159	2.413
A1	-	0.127
b	0.635	1.067
b3	4.953	5.461
c	0.457	0.610
c2	-	0.889
(c2)	0.457	0.610
D	5.969	6.223
D1	5.207	5.715
E	6.350	6.731
E1	4.318	5.207
e	2.29 REF.	
H	9.398	10.414
L	1.016	1.778
L2	0.25 REF.	
L3	0.889	1.270
L4	0.000	0.152
M	15°	
P	-	5°

Recommended Solder Pad Layout



7. Part Numbering and Marking



SiC	= SiC
2	= Gen 2
SD	= Schottky Barrier Diode
120	= Voltage Rating (1200 V)
C	= Package (TO-252-2L)
08	= Current Rating (8 A)
A	= AEC-Q101 qualified
YY	= Year
WW	= Week
D	= Special Code
ZZZZZZ-ZZ	= Lot Number

8. Packing Options

Part Number	Marking	Packing Mode	M.O.Q.
LSIC2SD120C08A	SIC2SD120C08A	Tape & Reel	2500

Littelfuse Expertise Applied | Answers Delivered
IXYS A Littelfuse Technology
Specifications are subject to change without notice.
Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics
© 2021 Littelfuse, Inc.
Revised: 3/1/2021

9. Packing Specifications

TO-252 Carrier Tape & Reel Specifications



1. Material: Black Conductive Polysterene
2. 10 sprocket hole pitch cumulative tolerance ± 0.20
3. Camber not to exceed 1 mm in 100 mm.
4. Pocket position relative to sprocket hole measured as true position of pocket, not pocket hole.
5. Device orientation: TRL (leads perpendicular to the sprocket)
6. General tolerance is ± 0.10 mm unless otherwise specified.

COVER TAPE SPECS:

Width	:	13.5 mm
Base Material	:	less than $1.2x10^{12}$ ohms/square Transparent polyester, static dissipative
Adhesive Layer	:	Polyethylene
Total Thickness	:	60 Micron
Tensile Strength	:	4–6 kg/mm²
Elongation	:	91%
Tearing Strength	:	11 kg/mm²
Shelf life	:	2 years



NOTES
1| WINDOW CLEARANCE ON BOTH SIDE DISK.
2| SURFACE RESISTANCE $>=10^2$ OHM AND $<1x10^{11}$ OHM. REFER TO IEC 61340-5-1.
3| RECYCLE LOGO WITH MATERIAL CODE "6" IN CIRCLE, ONE OR BOTH SIDE DISK.
4| DATE CODE IN CIRCLE ON ONE SIDE OF DISK.
5| TAPE WIDTH "16 mm" IN CIRCLE, TEXT HEIGHT 6 mm, ON BOTH SIDE DISK.
6| HUB SIZE INDICATION ON BOTH SIDE DISK.
7| AREA OF LABEL, MIN 110 x 55.
8| NUMBER OF GROOVES ACCORDING TO PRODUCER, EITHER 3 OR 6.
9| DEPRESSION LINEAR SCALE IS PREFERRED, 10 mm INTERVAL, HEIGHT OF LETTERING 3 mm.
NON CRITICAL DIMENSIONS ACCORDING TO PRODUCER.

For additional information please visit www.Littelfuse.com/powersemi

Disclaimer Notice - Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly forth in applicable Littelfuse product documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation.

Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics

Littelfuse Expertise Applied | Answers Delivered
IXYS A Littelfuse Technology

Specifications are subject to change without notice.
Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics
© 2021 Littelfuse, Inc.
Revised: 3/1/2021