

NOTES:
1. MATERIAL:SILICON RUBBER
2. YELLOW COLOR
3. 30 DURE HARD ◎

METRIC
COMPONENT

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
-				

BILL OF MATERIAL

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS.
DIMENSIONS IN BRACKETS [ ] ARE INCHES

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

◎	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
⟨ST⟩	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE

COPIES TO	MATL SPEC: SEE NOTES		
1 9 18 2 10 19 3 12 20 4 13 21 5 14 23 6 15 33 7 16 43 8 17 53	FINISH: N/A		
	DRW: EJIN	DATE: 03/29/12	SCALE: 1:1
	CHK	DATE	SUPER DR
	APPD	DATE	FINSH GOOD WT GRAMS/PIECE

TOLERANCES UNLESS OTHERWISE SPECIFIED (REF. ISO 2768-fH)

DIMENSION	UP TO 0.5 - 3	OVER 3 - 6 UP TO	OVER 6 - 30 UP TO	OVER 30 - 120 UP TO	OVER 120 - 400 UP TO
TOLERANCE					

3RD ANGLE PROJECTION

TITLE: #25 CABLE SEAL

Littelfuse®
DES PLAINES, ILLINOIS 60016

REVISION: A

DRWG. NO. OL-868-956

LTR	REVISION	CHK	APD
A	504799ERA NEW RELEASED EJIN		

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED