



- NOTES:
1. RATING: CONTINUOUS -175 AMP 6-12  
24-36 VOLTS DE, INTERMITTENT - 1000 AMPS  
6-12-24-36 VOLTS DC, 15 SEC "ON" 5 MIN "OFF"
  2. ALL STEEL PARTS PLATED
  3. HARDWARE ASSEMBLED
  4. ALL DIMENSIONS REFERENCE ONLY

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances	PROPRIETARY INFORMATION	Special Characteristics:	Cole Hersee Co.			
Rev.	Description of Change	ECN No.	Date					Unless otherwise specifically noted, the following are default tolerances:	This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.	<input checked="" type="checkbox"/> Critical Characteristic, relating to Safety and/or Regulatory Compliance <input checked="" type="checkbox"/> Significant Characteristic relating to Process Control <input checked="" type="checkbox"/> Control Dimension relating to Form-Fit - Function as defined by Cole Hersee Company and/or the Customer	20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com			
							2-places +/- 0.02"	3-places +/- 0.005"			Angular +/- 1'	Description:		
AA	CHANGE NOTE 3	09252	04/16/09				Metric: Shown in [ ] refers to equivalent English Dim: Tol	"REF." or an Asterisk (*) = Non-Toleranced Reference Dimension, shown for clarification purposes only.			SWITCH, MASTER DISCONNECT		Drawing / Part No.:	M-284
AB	ADDED "X" TO STUD TOPS	09563	12/7/09				NOTE: All tolerances are Non-Cumulative.	FORM CHT-6 (2/07)	Used On or Ref.:	Scale: 1:1	Drawn BY: VAK	Date Drawn: 10/19/54	Pg. 1 of 1	Current Rev. AB