

Model Series 464

File Number: E184655

COMPANY

LITTELFUSE INC

8755 W Higgins Rd, Suite 500
Chicago, IL 60631 United States

MODEL INFO

Series 464 with or without one prefix and with or without additional suffix letters.
Universal Modular Fuses

LOW-VOLTAGE FUSES CERTIFIED TO IEC STANDARDS	VALUE
IEC Standard	IEC 60127-1
Low-voltage Fuses	No
Universal Modular Fuses	Yes

GENERAL					
Mounting	Operating Characteristics	Amps (A)	AC Voltage (VAC)	DC Voltage (Vdc)	Interrupting Rating (Breaking Capacity) (A)
Surface	F-quick acting	1	250	--	100
Surface	F-quick acting	1.2	250	--	100
Surface	F-quick acting	1.6	250	--	100
Surface	F-quick acting	2	250	--	100
Surface	F-quick acting	2.5	250	--	100
Surface	F-quick acting	3.15	250	--	100
Surface	F-quick acting	4	250	--	100
Surface	F-quick acting	5	250	--	100
Surface	F-quick acting	6.3	250	--	100
Surface	F-quick acting	0.25	250	--	100
Surface	F-quick acting	0.35	250	--	100
Surface	F-quick acting	0.4	250	--	100
Surface	F-quick acting	0.5	250	--	100
Surface	F-quick acting	0.63	250	--	100
Surface	F-quick acting	0.8	250	--	100

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

