



P	PARK
P1	
L	LOW
L1	
H	HIGH
H1	
B	BATTERY
W	WASHER
CIRCUIT	DESCRIPTION
LEGEND	

- NOTES:
1. ALL STEEL PARTS PLATED
 2. PUSH KNOB TO WASH-"PARK", "LOW" & "HIGH"
 3. INSTALLATION TORQUE 2.7Nm (2 FT. LBS.)
 4. 20 AMPS @ 12 V.D.C.
 5. OPERATING TEMP RANGE -40°C TO + 85°C
 6. USE APPROPRIATE FEMALE TERMINALS THAT MATE TO STANDARD 1/4" X 0.032" BLADE TERMINALS

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances Unless otherwise specifically noted, the following are default tolerances:			PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.			Special Characteristics:			Cole Hersee Co.		
Rev.	Description of Change	ECN No.	Date					2-places +/- 0.02"	3-places +/- 0.005"	Angular +/- 1°	CC	X	KC	20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com					
D	ADD NOTE 5 & 6	09253	04/15/09											Description: DUAL W/W & WASHER SW, P.M MOTOR WITH DYNAMIC PARKING					
														Drawing / Part No.: 75236		Current Rev. D			
								FORM CHT-6 (2/07)	Used On or Ref.: EX-20879		Scale: 1:1	Drawn BY: RJF	Date Drawn: 04/22/85	Pg. 1 of 1					