



PIN NUMBER	CIRCUIT	12VDC RESISTIVE LOAD
2	START	5 AMPS
3	ACCESSARY	10 AMPS
4 & 5	IGNITION	10 AMPS
1 & 6	BATTERY	

PINS 1 & 6 CONNECTED TOGETHER INTERNALLY  
PINS 4 & 5 CONNECTED TOGETHER INTERNALLY

- NOTES:
1. TOLERANCES PLUS OR MINUS 0.015 [0.38]
  2. CONTACT AREA SEALED TO IP67
  3. BACK OF SWITCH SEALED WHEN MATING CONNECTOR IS INSTALLED
  4. FOR RESISTIVE LOAD RATING SEE CHART OR BACK OF SWITCH
  5. FOR PIN TERMINAL LOCATIONS & IDENTIFICATION SEE CHART
  6. MATERIALS: HOUSING BLACK THERMOPLASTIC  
INTERNAL STATIONARY CONTACTS: COPPER
  7. SWITCH TESTED TO SAE J259.
  8. SW. MATES WITH COLE HERSEE 31101 CONNECTOR ASSEMBLY
  9. START LOCKOUT FEATURE. SWITCH MUST GO TO "OFF" POSITION BEFORE THE START CIRCUIT CAN BE RE-ENERGIZED
  10. SW. MUST NOT BREAK CIRCUIT OR BE DAMAGED IF SHAFT IS TORQUED TO 15 IN-LBS [ 1.69Nm]
  11. SW. SAME AS 95061-04, EXCEPT TWO ADDITIONAL DRAIN HOLES ADDED.

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances Unless otherwise specifically noted, the following are default tolerances:			<b>PROPRIETARY INFORMATION</b> This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.	Special Characteristics:			<b>Cole Hersee Co.</b> 20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com
Rev.	Description of Change	ECN No.	Date				2-places +/- 0.02"	3-places +/- 0.005"	Angular +/- 1°	<input checked="" type="checkbox"/> Critical Characteristic, relating to Safety and/or Regulatory Compliance <input checked="" type="checkbox"/> Significant Characteristic relating to Process Control <input checked="" type="checkbox"/> Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer		Description:			
A	RELEASED DRAWING	10768	7/25/14									Metric: Shown in [ ] refers to equivalent English Dim Tol "REF." or an Asterisk (*) = Non-Toleranced Reference Dimension, shown for clarification purposes only. NOTE: All tolerances are Non-Cumulative.	<b>SW,ROT,IGN,PLSTC</b>		
												FORM CHT-6 (2/07) Used On or Ref.: <b>95061-04</b>	Scale: 1:1 Drawn BY:G.Auguste Date Drawn: 7/22/14 Pg. 1 of 1	Drawing / Part No.: <b>95061-05</b> Current Rev. <b>A</b>	