


# SiC Schottky Diode

 $V_{RRM} = 650 \text{ V}$   
 $I_{FAV} = 2 \times 80 \text{ A}$ 


Ultra fast switching  
 Zero reverse recovery

Part number  
**DCG160X650NA**



Backside: isolated

 E72873



### Features / Advantages:

- Ultra fast switching
- Zero reverse recovery
- Zero forward recovery
- Temperature independent switching behavior
- Positive temperature coefficient of forward voltage
- $T_{VJM} = 175^{\circ}\text{C}$

### Applications:

- Solar inverter
- Uninterruptible power supply (UPS)
- Welding equipment
- Switched-mode power supplies
- Medical equipment
- High speed rectifier

### Package: SOT-227B (minibloc)

- Isolation Voltage: 2500 V~
- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0
- Base plate with Aluminium nitride isolation for low thermal resistance
- Advanced power cycling

### Disclaimer Notice


Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

SiC Diode				Ratings			
Symbol	Definitions	Conditions	min.	typ.	max.		
$V_{RSM}$	max. non-repetitive reverse blocking voltage				650	V	
$V_{RRM}$	max. repetitive reverse blocking voltage				650	V	
$I_R$	reverse current	$V_R = V_{RRM}$		0.1 0.4	1.0 2.0	mA mA	
$V_F$	forward voltage	$I_F = 50\text{ A}$ $I_F = 100\text{ A}$	$T_{VJ} = 25^\circ\text{C}$	1.25		V	
				1.55	1.85	V	
		$I_F = 50\text{ A}$ $I_F = 100\text{ A}$	$T_{VJ} = 175^\circ\text{C}$	1.35		V	
				1.9	2.3	V	
$I_{FAV}$	average forward current	$T_C = 75^\circ\text{C}$ $T_C = 100^\circ\text{C}$ } rectangular, d = 0.5	$T_{VJ} = 175^\circ\text{C}$		80 67	A A	
$I_{F25}$	forward current	based on typ. $V_{F0}$ and $r_F$	$T_C = 25^\circ\text{C}$		134	A	
$I_{F80}$			$T_C = 80^\circ\text{C}$		101	A	
$I_{F100}$			$T_C = 100^\circ\text{C}$		87	A	
$I_{FSM}$	max forward surge current	t = 10 ms, half sine (50 Hz) $t_p = 10\ \mu\text{s}$ , pulse; $V_R = 0\text{V}$	$T_{VJ} = 25^\circ\text{C}$		650 3200	A A	
$V_{F0}$	threshold voltage		$T_{VJ} = 125^\circ\text{C}$ $175^\circ\text{C}$	0.83 0.77		V V	
$r_F$	slope resistance	for power loss calculation	$T_{VJ} = 125^\circ\text{C}$ $175^\circ\text{C}$	9.5 11.3		m $\Omega$ m $\Omega$	
$Q_C$	total capacitive charge	$V_R = 400\text{ V}$ , $I_F = 100\text{ A}$	$T_{VJ} = 25^\circ\text{C}$	220		nC	
$C$	total capacitance	$V_R = 0\text{ V}$ $V_R = 200\text{ V}$ $V_R = 400\text{ V}$ } f = 1 MHz; $T_{VJ} = 25^\circ\text{C}$		3950 400 360		pF pF pF	
$R_{thJC}$	thermal resistance junction to case				0.49	K/W	
$R_{thJH}$	thermal resistance junction to heatsink	with heatsink compound; IXYS test setup			0.62	K/W	

Package Outlines SOT-227B (minibloc)			Ratings			
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
$I_{RMS}$	RMS current	per terminal			100	A
$T_{stg}$	storage temperature		-40		150	°C
$T_{op}$	operation temperature		-40		150	°C
$T_{VJ}$	virtual junction temperature		-40		175	°C
<b>Weight</b>				30		g
$M_D$	mounting torque <sup>1)</sup>	screws to heatsink terminal connection screws			1.5 1.3	Nm Nm
$d_{Spp}$	creepage distance on surface	terminal to terminal	10.5			mm
$d_{Spb}$		terminal to backside	8.5			mm
$d_{App}$	striking distance through air	terminal to terminal	3.2			mm
$d_{Apb}$		terminal to backside	6.8			mm
$V_{ISOL}$	isolation voltage	$I_{ISOL} \leq 1 \text{ mA}; 50/60 \text{ Hz}$	3000 2500			V V
$C_p$	coupling capacity per switch	between shorted terminals of one diode and back side metallization		20		pF

<sup>1)</sup> further information see application note IXAN0073 on [www.ixys.com/TechnicalSupport/appnotes.aspx](http://www.ixys.com/TechnicalSupport/appnotes.aspx) (General / Isolation, Mounting, Soldering, Cooling)

## Product Marking





### Part description

D = Diode  
 C = SiC  
 G = Extreme fast  
 160 = Current Rating [A]  
 X = Parallel legs  
 650 = Reverse Voltage [V]  
 NA = SOT-227 (minibloc)


Ordering	Part Name	Marking on Product	Delivering Mode	Base Qty	Ordering Code
Standard	DCG160X650NA	DCG160X650NA	Tube	10	DCG160X650NA

### Equivalent Circuits for Simulation <sup>\*on die level</sup>

		$T_{VJ} = 125^\circ\text{C}$	$T_{VJ} = 175^\circ\text{C}$	
$V_{0 \max}$	threshold voltage	0.83	0.77	V
$R_{0 \max}$	slope resistance *	9.5	11.3	mΩ

**Outlines SOT-227B (minibloc)**


Dim.	Millimeter		Inches	
	min	max	min	max
A	31.50	31.88	1.240	1.255
B	7.80	8.20	0.307	0.323
C	4.09	4.29	0.161	0.169
D	4.09	4.29	0.161	0.169
E	4.09	4.29	0.161	0.169
F	14.91	15.11	0.587	0.595
G	30.12	30.30	1.186	1.193
H	37.80	38.23	1.488	1.505
J	11.68	12.22	0.460	0.481
K	8.92	9.60	0.351	0.378
L	0.74	0.84	0.029	0.033
M	12.50	13.10	0.492	0.516
N	25.15	25.42	0.990	1.001
O	1.95	2.13	0.077	0.084
P	4.95	6.20	0.195	0.244
Q	26.54	26.90	1.045	1.059
R	3.94	4.42	0.155	0.167
S	4.55	4.85	0.179	0.191
T	24.59	25.25	0.968	0.994
U	-0.05	0.10	-0.002	0.004
V	3.20	5.50	0.126	0.217
W	19.81	21.08	0.780	0.830
Z	2.50	2.70	0.098	0.106



**SiC Diode (per leg)**




Fig. 1 Typ. forward characteristics




Fig. 2 Typ. reverse characteristics




Fig. 3 Typ. current derating




Fig. 4 Power derating




Fig. 5 Typ. recovery charge vs. reverse voltage




Fig. 6 Typ. junction capacitance vs. reverse Voltage

**SiC Diode (per leg)**




Fig. 7 Typ. transient thermal impedance