



XCFR2.E171395
Terminal Blocks - Component

Page Bottom

Terminal Blocks - Component

See General Information for Terminal Blocks - Component

LITTELFUSE INC
SUITE 500
8755 W HIGGINS RD
CHICAGO, IL 60631 USA

E171395

Model No.	Wire Range	Wire Type	FW	TQ (In.-Lb)	V	A	UG	CA
OLS3126-XTP	350-6	Al-Cu	2	275	600	310	C	2(125), 4
OLS3305-XTP	Line: 2/0-6	Al-Cu	2	120	600	350	C	2(125), 4
	Line/Load: 8 Str	Cu		40				
	Line/Load: 10-14 Sol/Str	Cu		35				
	Line/Load: (2) No. 6 Str	Cu		120				
	Line/Load: (2) No. 8-14 Str	Cu		60				
	Load: 2-6 Str	Al		120				
	Load: 8 Str	Al		40				
OLS3320-XTP	(2) 250-1/0 Str	Al-Cu	2	275	600	510	C	2(125), 6 (16 x 12 x 6), 4
OLS3320-XTP	600-2	Al-Cu	2	375	600	420	C	2(125), 4, 6 (16 x 12 x 6),#
OLD3552-XTP	Line: 400-4 Str	Al-Cu	2	275	600	335	C	2(125), 4, 6 (16 x 12 x 6),#
	Load: 2-3 Str	Cu		50				
	Load: 4-6 Str	Cu		45				
	Load: 8 Str	Cu		40				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 8 Str	Cu		40				
	Load: (2) No. 10-14 Str	Cu		35				
	Load: 2-3 Str	Al		50				
	Load: 4-6 Str	Al		45				
	Load: 8 Str	Al		40				
OLD3554-XTP	Line: 350-6 Str	Al-Cu	2	275	600	310	C	2(125), 4, 6 (16 x 12 x 6),#

	Load: 2/0-6 Str	Cu		120				
	Load: 8 Str	Cu		40				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 6 Str	Cu		120				
	Load: (2) No. 8-14 Str	Cu		60				
	Load: 2/0-6 Str	Al		120				
	Load: 8 Str	Al		40				
0LD3555-XTP	Line: 2/0-6 Str	Al-Cu	2	120	600	350	C	2(125), 4, 6 (16 x 12 x 6),#
	Line: 8 Str	Cu		40				
	Line: 10-14 Sol/Str	Cu		35				
	Line: (2) No. 6 Str	Cu		120				
	Line: (2) No. 8-14 Str	Cu		60				
	Load: 4-8 Str	Al-Cu		35				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 10 Str	Cu		35				
	Load: (2-4) 12 Str	Cu		35				
	Load: (2-4) 14 Str	Cu		35				
0LD3565-XTP	Line: 600-2 Str	Al-Cu	2	375	600	420	C	2(125), 4
	Load: 250-2 Str	Al-Cu		275				
	Load: 3-6 Str	Cu		275				
	Load: (2) No. 2 Str	Cu		275				
	Load: (2) No. 4 Str	Cu		275				
	Load: (2) No. 6 Str	Cu		275				
0LD3575-XTP	Line: 600-2 Str	Al-Cu	2	375	600	420	C	2(125), 4
	Load: 2/0-6 Str	Al-Cu		120				
	Load: 8 Str	Al-Cu		40				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 6 Str	Cu		120				
	Load: (2) No. 8-14 Str	Cu		60				
0LD3585-XTP	Line: 600-2 Str	Al-Cu	2	375	600	420	C	2(125), 4, 6 (16 x 12 x 6),#
	Load: 2-6 Str	Al-Cu		60				
	Load: 8 Str	Al-Cu		35				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 8-14 Str	Cu		35				
0LD3587-XTP	Line: 500-4 Str	Al-Cu	2	375	600	380	C	2(125), 4, 6 (16 x 12 x 6),#
	Load: 350-6 Str	Al-Cu		275				

	Load: 2-3 Str	Al-Cu		50				
	Load: 4-6 Str	Al-Cu		45				
	Load: 8 Str	Al-Cu		40				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 8 Str	Cu		40				
	Load: (2) No. 10-14 Str	Cu		35				
OLD3588-XTP	Line: 600-2 Str	Al-Cu	2	375	600	420	C	2(125), 4, 6 (16 x 12 x 6),#
	Load: 1/0-1 Str	Al-Cu		120				
	Load: 2-6 Str	Al-Cu		60				
	Load: 8 Str	Al-Cu		35				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 8-14 Str	Cu		35				
OLD3595-XTP	Line: 600-2 Str	Al-Cu	2	375	600	420	C	2(125), 4, 6 (16 x 12 x 6),#
	Load: 4-8 Str	Al-Cu		35				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 10 Str	Cu		35				
	Load: (2-4) No. 12 Str	Cu		35				
	Load: (2-4) No. 14 Str	Cu		35				
OLD3596-XTP	Line: (2) 250-1/0 Str	Al-Cu	2	275	600	510	C	2(125), 4, 6 (16 x 12 x 6),#
	Load: 4-8 Str	Al-Cu		35				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 10 Str	Cu		35				
	Load: (2-4) No. 12 Str	Cu		35				
	Load: (2-4) No. 14 Str	Cu		35				
OLD3597-XTP	Line: (2) 250-1/0 Str	Al-Cu	2	275	600	510	C	2(125), 4, 6 (16 x 12 x 6),#
	Load: 2-6 Str	Al-Cu		60				
	Load: 8 Str	Al-Cu		35				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 8-14 Str	Cu		35				
OLD3598-XTP	Line: (2) 250-1/0 Str	Al-Cu	2	275	600	510	C	2(125), 4
	Load: 2/0-6 Str	Al-Cu		120				
	Load: 8 Str	Al-Cu		40				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 6 Str	Cu		120				
	Load: (2) No. 8-14 Str	Cu		60				

OLD3953-XTP	Line: 500-4 Str	Cu	2	375	600	380	C	2(125), 4, 6 (16 x 12 x 6),#
	Load: 2-3 Str	Cu		50				
	Load: 4-6 Str	Cu		45				
	Load: 8 Str	Cu		40				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 8 Str	Cu		40				
	Load: (2) No. 10-14 Str	Cu		35				
OLD3955-XTP	Line: 2/0-6 Str	Cu	2	120	600	350	C	2(125), 4, 6 (16 x 12 x 6),#
	Line: 8 Str	Cu		40				
	Line: 10-14 Sol/Str	Cu		35				
	Line: (2) No. 6 Str	Cu		120				
	Line: (2) No. 8-14 Str	Cu		60				
	Load: 4-8 Str	Cu		35				
	Load: 10-14 Sol/Str	Cu		35				
	Load: (2) No. 10 Str	Cu		35				
	Load: (2-4) No. 12 Str	Cu		35				
	Load: (2-4) No. 14 Str	Cu		35				
LS4557-X	(1)600-4, +++	Al-Cu	—	500	600	420	C	2(150)

X-The letter X is replaced by 1,2 or 3 to indicate the number of poles.

Unique Conditions of Acceptability - i.e., This terminal block is intended for use with miscellaneous fuses. These fuses are not intended for branch-circuit overcurrent protection. Markings concerning fuse replacement and location should be considered.

++ - These terminal blocks are acceptable for use with Class G, H, I, K, and DLO flexible stranded wire.

+++ - These terminal blocks are acceptable for use with Class G, H, I, K and DLO flexible stranded copper wire see report for wire range.

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
LS3123-X	(1)250-6, ++	Al-Cu	2	275	600	255	C	2(150)
LS3124-X	(1)250-6, +	Cu	2	275	600	255	C	2(150)
LS3126-X	(1)350-6, ++	Al-Cu	2	275	600	310	C	2(150)
LD3552-X	Line: (1)400-6, ++	Al-Cu	2	275	600	335	C	2(150), 6 (16 x 12 x 6),#
	Load: (4) 2-14	Al-Cu		275				
LD3553-X	Line: (1)400-6, ++	Al-Cu	2	275	600	350	C	2(150), 6 (16 x 12 x 6),#
	Load: 2	Al-Cu		50				
	Load: 4-6	Al-Cu		45				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				

LD3555-X	Line:2/0-6, ++	Al-Cu	2	120	600	350	C	2(150), 6 (16 x 12 x 6)
	Line: 8	Al-Cu		40				
	Line: 10-14	Al-Cu		35				
	Load: 4-14	Al-Cu		35				35
LD3953-X	Line: (1)500-6, ++	Cu	2	375	600	380	C	2(150), 6 (16 x 12 x 6), #
	Load: 2	Cu		50				
	Load: 4-6	Cu		45				
	Load: 8	Cu		40				
	Load: 10-14	Cu		35				
LD3955-X	Line: 2/0-6, ++	Cu	2	120	600	350	C	2(150), 6 (16 x 12 x 6), #
	Line: 8	Cu		40				
	Line: 10-14	Cu		35				
	Load: 4-14	Cu		35				
LD4551-X	Line: (1)500-4, ++	Al-Cu	2	375	600	380	C	2(150), 6 (16 x 12 x 6), #
	Load: 2	Al-Cu		50				
	Load: 4-6	Al-Cu		45				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				
LS4557-X	(1)600-4, ++	Al-Cu	2	500	600	420	C	2(150), 6 (16 x 12 x 6), #
LD4560-X	Line: (1)400-6, ++	Al-Cu	2	275	600	335	C	2(150), 6 (16 x 12 x 6), #
	Load: 2	Al-Cu		50				
	Load: 4-6	Al-Cu		45				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				
LS5129-X	(2)350-4, ++	Al-Cu	2	275	600	620	C	2(150)
LS5301-X	(2)500-6, ++	Al-Cu	2	375	600	760	C	2(150)
LD5552-X	Line: (1)500-4, ++	Al-Cu	2	375	600	380	C	2(150), 6 (16 x 12 x 6), #
	Load: 2	Al-Cu		50				
	Load: 4-6	Al-Cu		45				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				

LD5579-X	Line:(2)500-4, ++	Al-Cu	2	375	600	380	C	2(150), 6 (16 x 12 x 6), #
	Load: 2/0-6	Al-Cu		120				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				
LD5586-X	Line: (2)500-6, ++	Al-Cu	2	375	600	760	C	2(150), 6 (16 x 12 x 6), #
	Load: 2/0-6	Al-Cu		120				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				
LD5587-X	Line: (1)500-6, ++	Al-Cu	2	375	600	380	C	2(150)
	Line: (1)350-4, ++	Al-Cu	2	275	600	310	C	2(150)
	Load: 2/0-6	Al-Cu		120				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				
LD5592-X	Line: (2)500-6, ++	Al-Cu	2	375	600	760	C	2(150), 6 (16 x 12 x 6), #
	Load: 4-14	Al-Cu		35				
LD5594-X	Line: (1)500-4, ++	Al-Cu	2	375	600	380	C	2(150), 6 (16 x 12 x 6), #
	Load: 2	Al-Cu		50				
	Load: 4-6	Al-Cu		45				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				
LD5986-X	Line: (2)500-4, ++	Cu	2	375	600	760	C	2(150), 6 (16 x 12 x 6), #
	Load: 2/0-6	Al-Cu		120				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				
LD5992-X	Line: (2)500-4, ++	Cu	2	375	600	760	C	2(150), 6 (16 x 12 x 6), #
	Load: 2	Al-Cu		50				
	Load: 4-6	Al-Cu		45				
	Load: 8	Al-Cu		40				
	Load: 10-14	Al-Cu		35				

X-The letter X is replaced by 1, 2 or 3 to indicate number of poles.

+ - See report for flexible stranded wire class acceptability.

++ - These terminal blocks are acceptable for use with Class G, H, I, K, and DLO flexible stranded copper wire.

Unique Conditions of Acceptability - i.e., This terminal block is intended for use with miscellaneous fuses. These fuses are not intended for

branch-circuit overcurrent protection. Markings concerning fuse replacement and location should be considered.

(*)-Current rating of 1680A when utilizing copper wire, 1360A when utilizing aluminum wire.

+ See Report for wire range and torque values.

(A) - See below table:

Wire Size	Torque
2/0 AWG	120 in. lbs
1/0	120 in. lbs
1	120 in. lbs
2	120 in. lbs
4	120 in. lbs
6	120 in. lbs
8	40 in. lbs
10	35 in. lbs
12	35 in. lbs
14	35 in. lbs

X-The letter X is replaced by 1, 2 or 3 to indicate number of poles.

+Products evaluated to UL486E which allows for reduced torque values. See report for torque values.

++ - These terminal blocks are acceptable for use with Class G, H, I, K, and DLO flexible stranded wire.

#Unique condition of acceptability-These models are intended to be wired with crimped type fork or ring terminals for wires larger than 10 AWG.

Unique Conditions of Acceptability - i.e., This terminal block is intended for use with miscellaneous fuses. These fuses are not intended for branch-circuit overcurrent protection. Markings concerning fuse replacement and location should be considered.

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A		UG	CA
						Cu	Al		
LS0303-X	350-6, ++	Al-Cu	2	275	600	310		C	2(150)
LD0401-X	Line: 2/0-6, ++	Al-Cu	2	120	600	175		C	2(150), 6 (16 x 12 x 6), ##
	Line: 8	Al-Cu		40					
	Line: 10-14	Al-Cu		35					
	Line: 4-14	Al-Cu		35					
LD0402-X	Line: 2/0-6, ++	Al-Cu	2	120	600	175		C	2(150), 6 (16 x 12 x 6), ##
	Line: 8	Al-Cu		40					
	Line: 10-14	Al-Cu		35					
	Line: 4-14	Al-Cu		35					
LD0404-X	Line: 350-6, ++	Al-Cu	2	275	600	310		C	2(150), 6 (16 x 12 x 6), ##
	Load: 4-14	Al-Cu		35					

+XX denotes number of terminal positions.

++ - These terminal blocks are acceptable for use with Class G, H, I, K, and DLO flexible stranded copper wire.

#Unique Conditions of Acceptability — The acceptability of the solder connectors, feed-through solder connectors and feed-through wire wrap

connectors shall be determined in the end use application.

Unique Conditions of Acceptability - i.e., This terminal block is intended for use with miscellaneous fuses. These fuses are not intended for branch-circuit overcurrent protection. Markings concerning fuse replacement and location should be considered.

Cat. No.	Wire Range	Wire Type	FW	TQ (In. - Lb)	V	A		UG	CA
						Cu	Al		
LS2121-X	Line/Load: 1/0-2, ++	Cu	2	50	600	150	—	C	2(150)
	Line/Load: 4-6	Cu		45					
	Line/Load: 8	Cu		40					
	Line/Load: 10-14	Cu		35					
LS2552-X	Line/Load: 2, ++	Al-Cu	2	50	600	115	90	C	2(150), 6 (16 x 12 x 6)
	Line/Load: 4-6	Al-Cu		45					
	Line/Load: 8	Al-Cu		40					
	Line/Load: 10-14	Al-Cu		35					
LD2570-X	Line: 2/0-6, ++	Al-Cu	2	120	600	175	135	C	2(150), 6 (16 x 12 x 6), #
	Line: 8	Al-Cu		40					
	Line: 10-14	Al-Cu		35					
	Load: 4-14	Al-Cu		35					
LS2572-X	Line/Load: 2/0-6, ++	Al-Cu	2	120	600	175	135	C	2(150), 6 (16 x 12 x 6)
	Line/Load: 8	Al-Cu		40					
	Line/Load: 10-14	Al-Cu		35					
LD2970-X	Line: 2/0-6, ++	Cu	2	120	600	175	—	C	2(150), 6 (16 x 12 x 6), #
	Line: 8	Cu		40					
	Line: 10-14	Cu		35					
	Load: 4-14	Cu		35					

++ These terminal blocks are acceptable for use with Class G, H, I, K and DLO flexible stranded copper wires.

Unique Conditions of Acceptability - i.e., This terminal block is intended for use with miscellaneous fuses. These fuses are not intended for branch-circuit overcurrent protection. Markings concerning fuse replacement and location should be considered.

Cat. No.	Suitable Conductors kcmil/AWG		Overcurrent Protection Fuse Required Class/Max Amp Rating						SCCR, RMS Sym A	Volts Max
	Line	Load	J	T	RK1	RK5	G	CC		
LD1400-X, ++	2-6 Cu	10 Cu	200	200	200	60	60	30	100,000	600
	2-10 Cu	10-14 Cu	150	150	100	30	30	30	100,000	600
	4-10 (Class G, H, I,	10-14 (Class G, H, I,	150	150	100	30	60	30	100,000	600

	K)	K)								
LS2552-X	2-6 Cu	2-6 Cu	300	300	200	100	60	30	100,000	600
	2-10 Cu	2-10 Cu	150	150	100	30	60	30	100,000	600
	4-10 (Class G, H, I, K)	10-14 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD2570-X	2/0-6 Cu	4-10 Cu	200	200	200	100	60	30	100,000	600
	2/0-6	4-14	150	150	100	30	60	30	100,000	600
	1-6 Cu (Class G, H, I, K)	6-12 Cu (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD0401-X	2/0-6 Cu	4-10 Cu	200	200	200	100	—	30	100,000	600
			—	—	—	—	60	—	100,000	600
	1-6 Cu (Class G, H, I, K)	6-10 Cu (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD0404-X	350-3/0 Cu	4-8 Cu	400	400	400	200	60	30	100,000	600
	2/0-6 Cu	4-10 Cu	250	250	200	100	60	30	100,000	600
	1-6 Cu (Class G, H, I, K)	6-10 Cu (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD3553-X	400-3/0 Cu	2-8 Cu	500	500	400	200	—	30	100,000	600
			600	—	—	—	60	—	100,000	600
	400-6 Cu	2-10 Cu	350	3500	200	100	—	30	100,000	600
			—	—	—	—	60	—	100,000	600
	250-1/0 (Class G, H, I, K)	250-1/0 (Class G, H, I, K)	300	300	200	100	60	30	100,000	600
LS3123-X	250-6	250-6	300	300	200	100	60	30	100,000	600
	250-1/0 (Class G, H, I, K)	250-1/0 (Class G, H, I, K)	300	300	200	100	60	30	100,000	600
LS3124-X	250-6	250-6	300	300	200	100	60	30	100,000	600
	250-1/0 (Class G, H, I, K)	250-1/0 (Class G, H, I, K)	300	300	200	100	60	30	100,000	600
LS3124-X	350-1/0	350-1/0	400	400	400	100	60	30	100,000	600
	350-6	350-6	300	300	200	100	60	30	100,000	600
	250-1/0 (Class G, H, I, K)	250-1/0 (Class G, H, I, K)	300	300	200	100	60	30	100,000	600

LS3124-X	400-3/0 Cu	2-8 Cu	400	400	400	200	60	30	100,000	600
	400-6 Cu	2-10 Cu	200	200	200	100	60	30	100,000	600
	250-1/0 (Class G, H, I, K)	4-14 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD5552-X	500-3/0 Cu	2-6 Cu	400	400	400	200	60	30	100,000	600
	500-4 Cu	2-10 Cu	250	250	200	100	60	30	100,000	600
	(2)350-2 (Class G, H, I, K)	4 - 6 (Class G, H, I, K)	400	400	400	200	60	30	100,000	600
	(2)350-2 (Class G, H, I, K)	4 - 6 (Class G, H, I, K)	250	250	200	100	60	30	100,000	600
LD3953-X	500-3/0 Cu	2-8 Cu	400	400	400	200	60	30	100,000	600
	500-4 Cu	2-10 Cu	300	300	200	100	60	30	100,000	600
	250-1/0 (Class G, H, I, K)	4-14 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LS2572-XDIN	2/0-6 Cu	2/0-6 Cu	200	200	200	100	60	30	100,000	600
	1-6 (Class G, H, I, K)	1-6 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD2970-X	2/0-6 Cu	4-10 Cu	200	200	200	100	60	30	100,000	600
	1-6 Cu (Class G, H, I, K)	6-12 Cu (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD2970-XDIN	2/0-6 Cu	4-10 Cu	200	200	200	100	60	30	100,000	600
	1-6 (Class G, H, I, K)	6-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD2570-XDIN	2/0-6 Cu	4-10 Cu	200	200	200	100	60	30	100,000	600
	1-6 (Class G, H, I, K)	6-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD2580-XDIN	2/0-6 Cu	4-10 Cu	200	200	200	100	60	30	100,000	600
	1-6 (Class G, H, I, K)	6-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD2580-XDIN	2/0-2 Cu	4-8 Cu	400	400	400	100	60	30	100,000	600
	2/0-6 Cu	4-8 Cu	350	350	200	100	60	30	100,000	600

	4-10 (Class G, H, I, K)	10-14 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
OLD3555-XTP	2/0-2 Cu	4-8 Cu	400	400	400	100	60	30	100,000	600
	2/0-6 Cu	4-10 Cu	200	200	200	100	60	30	100,000	600
	1-6 (Class G, H, I, K)	6-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
OLD3955-XTP	2/0-2 Cu	4-8 Cu	400	400	400	100	60	30	100,000	600
	2/0-6 Cu	4-10 Cu	200	200	200	60	60	30	100,000	600
	1-6 (Class G, H, I, K)	6-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LS2972-XDIN	2/0-6 Cu	2/0-6 Cu	300	300	200	100	60	30	100,000	600
	4-6 Cu	10-14 Cu	200	200	200	100	60	30	100,000	600
	1-6 (Class G, H, I, K)	1-6 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD3552-X	400-3/0 Cu	2-6 Cu	400	400	400	100	60	30	100,000	600
	400-6 Cu	2-10 Cu	300	300	200	100	60	30	100,000	600
	250-1/0 (Class G, H, I, K)	4-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
OLD3552-XTP	400-3/0 Cu	2-8 Cu	400	400	400	100	60	30	100,000	600
	400-6 Cu	2-8 Cu	200	200	200	100	60	30	100,000	600
	250-1/0 (Class G, H, I, K)	1-6 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LS1300-X	2-6 Cu	2-6 Cu	200	200	200	100	60	30	100,000	600
	2-10 Cu	8-10 Cu	100	100	100	30	60	30	100,000	600
	4-10 (Class G, H, I, K)	4-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD5579-X	500-3/0 Cu	2/0-6 Cu	400	400	400	100	60	30	100,000	600
	2/0-4 Cu	8-10 Cu	200	200	200	100	60	30	100,000	600
	(2)350-2 (Class G, H, I, K)	1-6 (Class G, H, I, K)	400	400	400	100	60	30	100,000	600
	(2)350-2 (Class G, H, I, K)	1-10 (Class G, H, I, K)	250	250	200	100	60	30	100,000	600
LD0402-X	2/0-6 Cu	4-10 Cu	200	200	200	100	60	30	100,000	600

	1-6 (Class G, H, I, K)	6-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
OLD3595-XTP	600-3/0 Cu	4-8 Cu	500	500	400	200	60	30	100,000	600
	600-2 Cu	4-10 Cu	200	200	200	100	60	30	100,000	600
	350-2 (Class G, H, I, K)	6-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
OLD3587-XTP	500-3/0 Cu	350-6 Cu	500	500	400	200	60	30	100,000	600
	500-4 Cu	2-10 Cu	200	200	200	100	60	30	100,000	600
	350-2 (Class G, H, I, K)	1-6 (Class G, H, I, K)	500	500	400	200	60	30	100,000	600
	350-2 (Class G, H, I, K)	1-10 (Class G, H, I, K)	200	200	200	100	60	30	100,000	600
OLD3588-XTP	600-3/0 Cu	1/0-8 Cu	600	600	400	200	60	30	100,000	600
	600-2 Cu	1/0-10 Cu	200	200	200	100	60	30	100,000	600
	350-2 (Class G, H, I, K)	1-14 (Class G, H, I, K)	500	500	400	200	60	30	100,000	600
OLD3554-XTP	350-3/0 Cu	2/0-1 Cu	500	500	400	200	60	30	100,000	600
	350-6 Cu	2/0-10 Cu	200	200	200	100	60	30	100,000	600
	250-1 (Class G, H, I, K)	1-6 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD5594-X	500-3/0 Cu	2-8 Cu	500	500	400	200	60	30	100,000	600
	500-4 Cu	2-10 Cu	300	300	200	100	60	30	100,000	600
	(2)350-3/0 (Class G, H, I, K)	4-8 (Class G, H, I, K)	500	500	600	200	60	30	100,000	600
	(2)350-2 (Class G, H, I, K)	4-10 (Class G, H, I, K)	300	300	200	100	60	30	100,000	600
LD4551-X	500-3/0 Cu	2-8 Cu	500	500	400	200	60	30	100,000	600
	500-4 Cu	2-10 Cu	200	200	200	100	60	30	100,000	600
	350-2 (Class G, H, I, K)	4-14 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
OLS3320-XTP	2)250- 1/0 Cu	2)250- 1/0 Cu	500	500	400	200	60	30	100,000	600
	(2) 3/0- 1/0 Cu (Class G, H, I,	(2) 3/0- 1/0 Cu (Class G, H, I,	500	500	400	200	60	30	100,000	600

	K)	K)								
0LD3596-XTP	250-1/0 Cu	4-10 Cu	450	450	400	100	60	30	100,000	600
	3/0-1/0 (Class G, H, I, K)	6-14 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
0LD3597-XTP	250-1/0 Cu	2-8 Cu	350	350	200	100	60	30	100,000	600
	3/0-1/0 (Class G, H, I, K)	4-14 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
0LD3585-XTP	600-3/0 Cu	2-8 Cu	400	400	4000	200	60	30	100,000	—
	600-2 Cu	2-10 Cu	200	200	200	100	60	30	100,000	600
	350-2 (Class G, H, I, K)	4-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
0LD3953-XTP	500-3/0 Cu	2-10 Cu	400	400	400	100	60	30	100,000	600
	500-4 Cu	2-10 Cu	200	200	200	100	60	30	100,000	600
	350-2 (Class G, H, I, K)	4-10 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LS2572-X	2/0-6 Cu	2/0-6 Cu	300	300	200	100	60	30	100,000	600
	1-6 Cu (Class G, H, I, K)	1-6 Cu (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LD3555-X	2)2/0-2 Cu	4-8 Cu	400	400	400	100	60	30	100,000	600
	2)2/0-6 Cu	4/8 Cu	350	350	200	100	60	30	100,000	600
	1-6 (Class G, H, I, K)	6-8 (Class G, H, I, K)	150	150	100	30	60	30	100,000	600
LS5129-X	2)350-4 Cu	2)350-4 Cu	450	450	400	200	60	30	100,000	600
	2)350-4 Cu	2)350-4 Cu	600	600	—	—	—	—	50,000	600
	250-2 (Class G, H, I, K)	250-2 (Class G, H, I, K)	600	600	400	200	60	30	100,000	600
LS5301-X	2)500-4 Cu	2)500-4 Cu	500	500	400	200	60	30	100,000	600
	(2)350-2 (Class G, H, I, K)	(2)350-2 (Class G, H, I, K)	500	500	600	200	60	30	100,000	600
LD5586-X	500-250 Cu	2/0-4 Cu	600	600	400	200	60	30	100,000	600
	500-4 Cu	2/0-10 Cu	350	350	200	100	60	30	100,000	600
	350-2 (Class G, H, I, K)	6-14 (Class G, H, I, K)	600	600	400	200	60	30	100,000	600
LD5986-X	500-250 Cu	2/0-4 Cu	500	500	400	200	60	30	100,000	600

	500-4 Cu	2/0-6 Cu	450	450	400	200	60	30	100,000	600
	(2)350-250 (Class G, H, I, K)	1-14 (Class G, H, I, K)	500	500	400	200	60	30	100,000	600
	(2)350-2 (Class G, H, I, K)	1-6 (Class G, H, I, K)	450	450	400	200	60	30	100,000	600
LD5592-X	500-250 Cu	4-8 Cu	400	400	200	100	60	30	100,000	600
	500-4 Cu	4-10 Cu	350	350	200	100	60	30	100,000	600
	(2)350-250 (Class G, H, I, K)	6-8 (Class G, H, I, K)	400	400	200	100	60	30	100,000	600
	(2)350-2 (Class G, H, I, K)	6-10 (Class G, H, I, K)	350	350	200	100	60	30	100,000	600
LD5992-X	500-250 Cu	2-8 Cu	600	600	—	—	—	—	50,000	600
	500-4 Cu	2-10 Cu	400	400	400	200	60	30	100,000	600
	(2)350-250 (Class G, H, I, K)	1-4 (Class G, H, I, K)	600	600					50,000	600
	(2)350-2 (Class G, H, I, K)	4-10 (Class G, H, I, K)	400	400	400	200	60	30	100,000	600
0LS3320-XTP	600-2 Cu	600-2 Cu	600	600	—	—	—	—	50,000	600
			400	400	400	200	60	30	100,000	600
	350-2 (Class G, H, I, K)	350-2 (Class G, H, I, K)	400	400	400	200	60	30	100,000	600
LD4557-X	600-2 Cu	600-2 Cu	600	600	—	—	—	—	50,000	600
			400	400	400	200	60	30	100,000	600
	400-2 (Class G, H, I, K)	400-2 (Class G, H, I, K)	400	400	400	200	60	30	100,000	600

++ - These terminal blocks are acceptable for use with Class G, H, I, K, and DLO flexible stranded wire.

Cat. No.	Suitable Conductors kcmil/AWG		Overcurrent Protection Circuit Breaker Required			SCCR, RMS Sym A	Volts Max
	Line	Load	Mfr	Type	Max Amp		
LD2570-X	2/0 - 1	4 - 10	Allen Bradley	140U-J3D3 140U-J6D3	250	18000	480
	2 - 4	4 - 10	Allen Bradley	140U-J3D3 140U-J6D3	250	18000	480
	2 - 6	4 - 12	Allen Bradley	140U-H3C3	125	30000	480
	6	14	Allen Bradley	140U-H6C3	125	22000	480

LD1400-X	2-10	10-14	Allen Bradley	140U-H3C3	125	25000	480
	2-10	10	Allen Bradley	140U-H6C3	125	22000	480
LD3553-X	400 - 2	2-8	Allen Bradley	140U-K6X3	400	18000	480
	4/0 - 4	2-10	Allen Bradley	140U-J6X3	250	25000	480
LD3953-X	2/0 - 4	2-8	Square D	JDL36250	250	18000	480
			Square D	JGL36250	250	35000	480
			Square D	JJL36250	250	65000	480
			Square D	JLL36250	250	65000	480

Cat. No.	Suitable Conductors kcmil/AWG		Overcurrent Protection Circuit Breaker Required			SCCR, RMS Sym A	Volts Max
	Line	Load	Mfr	Type	Max Amp		
LS1300-X	1) 2 - 6	1) 2 - 6	Square D	JDL36250	250	18 kA	480
			Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
LS1300-X	1) 8 - 10	1) 8 - 10	Square D	HDL36100	100	18 kA	480
			Square D	HGL36100	100	35 kA	480
			Square D	HJL36100	100	65 kA	480
			Square D	HLL36100	100	65 kA	480
LD1400-X	1) 2 - 6	4) 10	Square D	JDL36250	250	18 kA	480
			Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
LD1400-X	1) 8 - 10	4) 14	Square D	JDL36250	250	18 kA	480
			Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
			Square D	HDL36100	100	18 kA	480
			Square D	HGL36100	100	35 kA	480
			Square D	HJL36100	100	65 kA	480
			Square D	HLL36100	100	65 kA	480
LD0401-X	1) 2/0 - 6	6) 4 - 10	Square D	JDL36250	250	18 kA	480
			Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
			Square D	JDL36250	250	18 kA	480
LD5579-X	1) 2/0 - 4	6) 8	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480

			Square D	JLL36250	250	65 kA	480
			Square D	JDL36250	250	18 kA	480
LD5552-X	1) 2/0 - 4	12) 2 - 8	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
			Square D	JDL36250	250	18 kA	480
	1) 350 - 4	12) 2 - 10	Allen Bradley	140U-J3D3	250	35 kA	480
	1) 500 - 4	12) 2 - 6	Allen Bradley	140U-K3D3	400	35 kA	480
LD4560-X	1) 2/0 - 6	6) 2 - 10	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
			Square D	JDL36250	250	18 kA	480
LD3552-X	1) 2/0 - 4	4) 2 - 8	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
			Square D	JDL36250	250	18 kA	480
LD3555-X	2) 1/0 - 8	6) 4 - 10	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
			Square D	JDL36250	250	18 kA	480
	2) 2/0 - 2	6) 4 - 8	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
LD3955-X			Square D	JLL36250	250	65kA	480
			Square D	JDL36175	175	18 kA	480
	2) 4 - 6	6) 10 - 12	Square D	JGL36175	175	35 kA	480
			Square D	JJL36175	175	65 kA	480
	2) 2/0 - 2	6) 4 - 8	Square D	JLL36175	175	65 kA	480
			Square D	JDL36250	250	18 kA	480
LD3553-X	1) 2/0 - 6	6) 2 - 10	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
			Square D	JDL36250	250	18 kA	480
LD2570-X	2/0 - 10	4 - 10	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
			Square D	JDL36250	250	18 kA	480
LS2121-X	1/0 - 8	1/0 - 8	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480

			Square D	JDL36250	250	18 kA	480
LD2970-X	2/0 - 8	4 - 8	Square D	JGL36250	250	35 kA	480
			Square D	JJL36250	250	65 kA	480
			Square D	JLL36250	250	65 kA	480
LD0404-X	350 - 6	4 - 12	GE	SFPA36AT0250	250	100ka	480
Note: X Denotes number of poles							
Note: n) Denotes number of termination points							

Marking: Company name and catalog designation (catalog designation may appear on shipping carton).

Last Updated on 2013-11-14

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".