
PART NO.	MAX. CONTINUOUS OPERATING VOLTAGE (AC)	NOMINAL AC VOLTAGE	ELECTRICAL SYSTEM
SPDN-D120-1P	180	120	SINGLE PHASE
SPDN-D120-2S	180	240/120	SPLIT PHASE
SPDN-D120-3Y	150	208/120	3 PHASE WYE
SPDN-D240-1P	350	240	SINGLE PHASE
SPDN-D240-2S	350	480/240	SPLIT PHASE
SPDN-D277-3Y	350	480/277	3 PHASE WYE



REV A


DATE


5/16/23

DESCRIPTION


526444GCP - RELEASE MRY


107.9 ± 0.3 [4.25 ± 0.010]
-88.2±0.3 [3.47±0.010]
$-69.9 \pm 0.3$ $-20.010$






## WIRING CONFIGURATION







## NOTES:

- 1. STANDARD LEAD LENGTH: 18-20"
- 2. ENCLOSURE RATING: POLYCARBONATE 4X

**BILL OF MATERIAL** CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE DENOTES CRITICAL CHARACTERISTICS. DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE CPK DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS CP SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. MATL SPEC DRW myork DATE 2/28/2023 SCALE NTS FINISH GOOD WT UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [ ] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994 3RD ANGLE PROJECTION  $\oplus \Box$ TITLE SURGE PROTECTION DEVICE, UL TYPE 1 OUTLINE

DESCRIPTION

QTY/M U/M



NO COMPONENT NO

